

IN THE CLAIMS

Please cancel without prejudice Claims 1-64.

Please add new Claims 65-101 as follows:

--65. A remote power meter monitoring system, comprising:  
a multiplicity of radio frequency transmit-only devices  
configured to transmit information, each radio frequency transmit-  
only device comprising,

a timer comprising a memory that holds a pseudo  
random time interval value, said timer configured to autonomously  
initiate transmission of said information after expiration of a  
time duration corresponding to said pseudo random time interval  
value held in said memory,

a pseudo-randomization means for generating and  
loading said pseudo random time interval value into said timer,  
and

a retransmission means for redundantly transmitting  
said information a predetermined number of times;

at least one sensing element configured to provide sensor  
data to said radio frequency transmit-only device, said  
transmitted information comprising said sensor data, an  
identification address being assigned to said radio frequency  
transmit-only device to which the sensor data is provided, and  
error detection code bits;

at least two receivers each configured to receive said  
transmitted information, and configured to validate said  
information based on said identification address and said error  
detection code bits contained in said transmitted information,  
said receivers providing redundant reception of said transmitted

A

Sub  
B  
373-052097  
A2  
Cont

information; and

B2  
Cont  
a monitoring means for monitoring said information as received and validated by at least one of said receivers.

66. A remote power meter monitoring system, comprising:

A2  
Cont  
a multiplicity of radio frequency transmit-only devices configured to transmit information in a direct sequence spread spectrum signal at plural frequencies, each radio frequency transmit-only device comprising,

a processor configured to generate said information to be transmitted,

a crystal oscillator configured to generate spread spectrum timing for said information generated by said processor,

a timer configured to hold a pseudo random time interval value, said timer configured to initiate transmission of said information after expiration of a time duration corresponding to said pseudo random time interval value,

a pseudo-randomization means for generating and loading said pseudo random time interval value into said timer,

a retransmission means for redundantly transmitting said information a predetermined number of times, and

a wake-up circuit configured to initiate said crystal oscillator and said processor in respective active states upon expiration of said time duration so as to transmit said information, and configured to place said crystal oscillator and said processor in a reduced current state between transmissions;

at least one sensing element configured to provide sensor

08559378 052097

B2  
cont

data to said radio frequency transmit-only device, said transmitted information comprising said sensor data, an identification address being assigned to said radio frequency transmit-only device to which the sensor data is provided, and error detection code bits;

at least two receivers each configured to receive said transmitted information, and configured to validate said information based on said identification address and said error detection code bits contained in said transmitted information, said receivers providing redundant reception of said transmitted information; and

a monitoring means for monitoring said information as received and validated by at least one of said receivers.

3  
67. A remote power meter monitoring system, comprising:

08859378-052097

a multiplicity of radio frequency transmit-only devices configured to transmit information in a direct sequence spread spectrum signal at plural frequencies, said information comprising a first field comprising a preamble configured to establish chip code timing synchronization and a second field comprising data, said first field being transmitted prior to said second field, said preamble having a length measured in bit times that is at least equal in length to a number of chips in a chip code sequence used to produce said spread spectrum signal, each radio frequency transmit-only device comprising,

a timer comprising a memory for holding a pseudo random time interval value, said timer configured to autonomously

13

initiate transmission of said information after expiration of a time duration corresponding to said pseudo random time interval value held in said memory,

a pseudo-randomization means for generating and loading said pseudo random time interval value into said timer, and

a retransmission means for redundantly transmitting said information a predetermined number of times;

at least one sensing element configured to provide sensor data to said radio frequency transmit-only device, said transmitted information comprising said sensor data, an identification address being assigned to said radio frequency transmit-only device to which the sensor data is provided, and error detection code bits;

at least two receivers each <sup>configurable</sup> ~~configured~~ to receive said transmitted information, and <sup>configurable</sup> ~~configured~~ to validate said information based on said identification address and said error detection code bits contained in said transmitted information; said at least two receivers providing redundant reception of said transmitted information, said at least two receivers configured to establish chip code synchronization to said direct sequence spread spectrum signal using said preamble; and

a monitoring means for monitoring said information as received and validated by at least one of said receivers.

- <sup>4</sup>  
~~68~~. A remote power meter monitoring system, comprising:  
a multiplicity of radio frequency transmit-only devices

configured to transmit information in a direct sequence spread spectrum signal at plural frequencies, said information comprising a first field comprising a preamble configured to establish chip code timing synchronization and a second field comprising data, said first field being transmitted prior to said second field, said preamble having a length measured in bit times that is at least equal in length to a number of chips in a chip code sequence plus approximately five bit times, each radio frequency transmit-only device comprising,

A2  
Cont

a timer comprising a memory for holding a pseudo random time interval value, said timer configured to autonomously initiate transmission of said information after expiration of a time duration corresponding to said pseudo random time interval value held in said memory,

665938-5500  
260250" 225500

a pseudo-randomization means for generating and loading said pseudo random time interval value into said timer, and

a retransmission means for redundantly transmitting said information a predetermined number of times;

at least one sensing element configured to provide sensor data to said radio frequency transmit-only device, said transmitted information comprising said sensor data, an identification address being assigned to said radio frequency transmit-only device to which the sensor data is provided, and error detection code bits;

B  
B

at least two receivers each <sup>configurable</sup> configured to receive said transmitted information, and <sup>configurable</sup> configured to validate said

information based on said identification address and said error detection code bits contained in said transmitted information, said receivers providing redundant reception of said transmitted information, said receivers configured to establish chip code lock and fine chip code synchronization using said preamble; and

a monitoring means for monitoring said information as received and validated by at least one of said receivers.

~~5~~ 49. A remote power meter monitoring system, comprising:

a multiplicity of radio frequency transmit-only devices configured to transmit information in a direct sequence spread spectrum signal at plural frequencies, said information comprising a first field comprising a preamble configured to establish chip code timing synchronization and a second field comprising data, said first field being transmitted prior to said second field, said preamble having a length measured in bit times that is less than  $n$  bit times, where  $n$  equals a number of chips in a chip code sequence, each radio frequency transmit-only device comprising,

a timer comprising a memory for holding a pseudo random time interval value, said timer configured to autonomously initiate transmission of said information after expiration of a time duration corresponding to said pseudo random time interval value held in said memory,

a pseudo-randomization means for generating and loading said pseudo random time interval value into said timer, and

a retransmission means for redundantly transmitting

46

said information a predetermined number of times;

at least one sensing element configured to provide sensor data to said radio frequency transmit-only device, said transmitted information comprising said sensor data, an identification address being assigned to said radio frequency transmit-only device to which the sensor data is provided, and error detection code bits;

at least two receivers each <sup>Configurable</sup> configured to receive said transmitted information, and <sup>Configurable</sup> configured to validate said information based on said identification address and said error detection code bits contained in said transmitted information, said receivers providing redundant reception of said transmitted information, said receivers comprising respective parallel correlation means for establishing chip code synchronization using said preamble; and

a monitoring means for monitoring said information as received and validated by at least one of said receivers.

<sup>6</sup>  
~~70~~. A remote power meter monitoring system, comprising:

a multiplicity of radio frequency transmit-only devices configured to transmit information in a direct sequence spread spectrum signal at plural frequencies, each radio frequency transmit-only device comprising,

a processor configured to generate said information to be transmitted,

a crystal oscillator configured to generate spread spectrum timing for said information generated by said processor,

a timer configured to delay transmission of said information by a predetermined delay after said expiration of <sup>a</sup> said time duration so as to allow for crystal stabilization, transmit carrier frequency stabilization and chip code timing generation stabilization,

a retransmission means for redundantly transmitting said information a predetermined number of times, and

a wake-up circuit configured to initiate said crystal oscillator and said processor in respective active states upon expiration of said time duration so as to transmit said information, and configured to place said crystal oscillator and said processor in a reduced current state between transmissions;

at least one sensing element configured to provide sensor data to said radio frequency transmit-only device, said transmitted information comprising said sensor data, an identification address being assigned to said radio frequency transmit-only device to which the sensor data is provided, and error detection code bits;

at least two receivers each of which being configured to receive said transmitted information, and configured to validate said information based on said identification address and said error detection code bits contained in said transmitted information, said receivers providing redundant reception of said transmitted information; and

a monitoring means for monitoring said information as received and validated by at least one of said receivers.

a2  
cont

08559378.052097



B <sup>7</sup> 71. The system according to Claims <sup>1</sup> ~~66~~, <sup>3</sup> ~~67~~, <sup>4</sup> ~~68~~, or <sup>5</sup> ~~69~~,  
wherein respective of said radio frequency transmit-only devices,  
further comprises:

a processor configured to generate said information to be  
transmitted,

a crystal oscillator configured to generate spread spectrum  
timing for said information generated by said processor,

an oscillator configured to generate a carrier on which said  
information to be transmitted is modulated;

a wake-up circuit configured to initiate said crystal  
oscillator and said oscillator in respective active states upon  
expiration of said time duration so as to transmit said  
information, and configured to place said crystal oscillator and  
said oscillator in a reduced current state between transmissions,  
said information being transmitted after a predetermined delay  
with respect to when said crystal oscillator and said oscillator  
are placed in said respective active states so as to allow for  
stabilization in said oscillator and said crystal oscillator prior  
to information transmission.

72. The system according to Claims 67, 68, 69, or 70,  
wherein a chip code sequence used to produce said preamble is a  
same sequence as a data bearing chip code sequence.

<sup>9</sup> 73. A remote power meter monitoring system, comprising:  
a multiplicity of radio frequency transmit-only devices  
~~configured to transmit information~~ <sup>in a message</sup>, each radio frequency transmit-

only device comprising,

a timer configured to autonomously initiate transmission of said information after expiration of a time duration, and

a pseudo-randomization means for randomizing the time <sup>duration</sup> ~~interval~~ between transmissions of said message,

a retransmission means for redundantly transmitting said message a predetermined number of times,

a processor configured to generate said information to be transmitted,

a crystal oscillator configured to generate spread spectrum timing for said information generated by said processor,

a carrier generator mechanism configured to generate a carrier on which said information to be transmitted is modulated, and

a wake-up circuit configured to initiate said crystal oscillator and said carrier generator mechanism in respective active states upon expiration of said time duration so as to transmit said information, and configured to place said crystal oscillator and said carrier generator mechanism in a reduced current state between transmissions, said information being transmitted after a predetermined delay with respect to when said crystal oscillator and said carrier generator mechanism are placed in said respective active states so as to allow for stabilization in said carrier generator mechanism and said crystal oscillator prior to information transmission;

at least one sensing element configured to provide sensor

00059378 050097

data to said radio frequency transmit-only device, said transmitted information comprising said sensor data, an identification address being assigned to said radio frequency transmit-only device to which the sensor data is provided, and error detection code bits;

a receiver configured to receive said transmitted information, and configured to validate said information based on said identification address and said error detection code bits contained in said transmitted information; and

a monitoring means for monitoring said information as received and validated by said receiver.

74. A remote power meter monitoring system, comprising:

a multiplicity of radio frequency transmit-only devices configured to transmit information in a direct sequence spread spectrum signal at plural frequencies, each radio frequency transmit-only device comprising,

a processor configured to generate said information to be transmitted,

a crystal oscillator configured to generate spread spectrum timing for said information generated by said processor,

a timer configured to initiate transmission of said information after expiration of a time duration,

a retransmission means for redundantly transmitting said information a predetermined number of times,

a pseudo-randomization means for randomizing the time interval between redundant transmissions,

a receiver configured to receive said transmitted information, and configured to validate said information based on said identification address and said error detection code bits

contained in said transmitted information; and

B4  
Cont.  
a monitoring means for monitoring said information as received and validated by said receiver.

11  
15. A remote power meter monitoring system, comprising:  
a multiplicity of radio frequency transmit-only devices configured to transmit information in a direct sequence spread spectrum signal at plural frequencies, said information comprising a first field comprising a preamble configured to establish chip code timing synchronization and a second field comprising data, said first field being transmitted prior to said second field, said preamble having a length measured in bit times that is at least equal in length to a number of chips in a chip code sequence used to produce said spread spectrum signal, each radio frequency transmit-only device comprising,

A2  
Cont.  
200250 92E5590  
a timer configured to autonomously initiate transmission of said information after expiration of a time duration,

a retransmission means for redundantly transmitting said information a predetermined number of times,

a pseudo-randomization means for randomizing the time interval between redundant transmissions,

a processor configured to generate said information to be transmitted,

a crystal oscillator configured to generate spread spectrum timing for said information generated by said processor,

a carrier generator mechanism configured to generate

a carrier on which said information to be transmitted is modulated, and

a wake-up circuit configured to initiate said crystal oscillator and said carrier generator mechanism in respective active states upon expiration of said time duration so as to transmit said information, and configured to place said crystal oscillator and said carrier generator mechanism in a reduced current state between transmissions, said information being transmitted after a predetermined delay with respect to when said crystal oscillator and said carrier generator mechanism are placed in said respective active states so as to allow for stabilization in said carrier generator mechanism and said crystal oscillator prior to information transmission;

at least one sensing element configured to provide sensor data to said radio frequency transmit-only device, said transmitted information comprising said sensor data, an identification address being assigned to said radio frequency transmit-only device to which the sensor data is provided, and error detection code bits;

a receiver configured to receive said transmitted information, and configured to validate said information based on said identification address and said error detection code bits contained in said transmitted information, said receiver configured to establish chip code synchronization to said direct sequence spread spectrum signal using said preamble; and

a monitoring means for monitoring said information as received and validated by said receiver.

<sup>12</sup>  
~~18~~. A remote power meter monitoring system, comprising:

a multiplicity of radio frequency transmit-only devices configured to transmit information in a direct sequence spread spectrum signal at plural frequencies, said information comprising a first field comprising a preamble configured to establish chip code timing synchronization and a second field comprising data, said first field being transmitted prior to said second field, said preamble having a length measured in bit times that is at least equal in length to a number of chips in a chip code sequence plus approximately five bit times, each radio frequency transmit-only device comprising,

a timer configured to autonomously initiate transmission of said information after expiration of a time duration,

a retransmission means for redundantly transmitting said information a predetermined number of times,

a pseudo-randomization means for randomizing the time interval between redundant transmissions,

a processor configured to generate said information to be transmitted,

a crystal oscillator configured to generate spread spectrum timing for said information generated by said processor,

a carrier generator mechanism configured to generate a carrier on which said information to be transmitted is modulated, and

a wake-up circuit configured to initiate said crystal oscillator and said carrier generator mechanism in

03559378-052097

respective active states upon expiration of said time duration so as to transmit said information, and configured to place said crystal oscillator and said carrier generator mechanism in a reduced current state between transmissions, said information being transmitted after a predetermined delay with respect to when said crystal oscillator and said carrier generator mechanism are placed in said respective active states so as to allow for stabilization in said carrier generator mechanism and said crystal oscillator prior to information transmission;

at least one sensing element configured to provide sensor data to said radio frequency transmit-only device, said transmitted information comprising said sensor data, an identification address being assigned to said radio frequency transmit-only device to which the sensor data is provided, and error detection code bits;

a receiver configured to receive said transmitted information, and configured to validate said information based on said identification address and said error detection code bits contained in said transmitted information, said receiver configured to establish chip code lock and fine chip code synchronization using said preamble; and

a monitoring means for monitoring said information as received and validated by said receiver.

<sup>13</sup>  
~~27~~. A remote power meter monitoring system, comprising:

a multiplicity of radio frequency transmit-only devices configured to transmit information in a direct sequence spread



spectrum signal at plural frequencies, said information comprising a first field comprising a preamble configured to establish chip code timing synchronization and a second field comprising data, said first field being transmitted prior to said second field, said preamble having a length measured in bit times that is less than  $n$  bit times, where  $n$  equals a number of chips in a chip code sequence, each radio frequency transmit-only device comprising,

a timer configured to autonomously initiate transmission of said information after expiration of a time duration,

a retransmission means for redundantly transmitting said information a predetermined number of times,

a pseudo-randomization means for randomizing the time interval between redundant transmissions,

a processor configured to generate said information to be transmitted,

a crystal oscillator configured to generate spread spectrum timing for said information generated by said processor,

a carrier generator mechanism configured to generate a carrier on which said information to be transmitted is modulated, and

a wake-up circuit configured to initiate said crystal oscillator and said carrier generator mechanism in respective active states upon expiration of said time duration so as to transmit said information, and configured to place said crystal oscillator and said carrier generator mechanism in a reduced current state between transmissions, said information

022  
CONF  
00059378.052097

56

being transmitted after a predetermined delay with respect to when said crystal oscillator and said carrier generator mechanism are placed in said respective active states so as to allow for stabilization in said carrier generator mechanism and said crystal oscillator prior to information transmission;

at least one sensing element configured to provide sensor data to said radio frequency transmit-only device, said transmitted information comprising said sensor data, an identification address being assigned to said radio frequency transmit-only device to which the sensor data is provided, and error detection code bits;

a receiver configured to receive said transmitted information, and configured to validate said information based on said identification address and said error detection code bits contained in said transmitted information, said receiver comprising respective parallel correlation means for establishing chip code synchronization using said preamble; and

a monitoring means for monitoring said information as received and validated by said receiver.

<sup>14</sup>  
~~28~~. The system according to Claims <sup>1</sup>~~65~~, <sup>2</sup>~~66~~, <sup>3</sup>~~67~~, <sup>4</sup>~~68~~, <sup>5</sup>~~69~~, <sup>6</sup>~~70~~, <sup>9</sup>~~71~~, <sup>10</sup>~~72~~, <sup>11</sup>~~73~~, <sup>12</sup>~~74~~, or <sup>13</sup>~~75~~, wherein said radio frequency transmit-only device comprises an information priority mechanism that is configured to increase a rate of information transmission when said sensor data input to said radio frequency transmit-only device changes.

<sup>15</sup>  
~~78~~. The system according to Claims <sup>1</sup>~~65~~, <sup>2</sup>~~66~~, <sup>3</sup>~~67~~, <sup>4</sup>~~68~~, <sup>5</sup>~~69~~, <sup>6</sup>~~70~~,  
<sup>9</sup>~~73~~, <sup>10</sup>~~74~~, <sup>11</sup>~~75~~, <sup>12</sup>~~76~~, or <sup>13</sup>~~77~~, wherein said radio frequency transmit-only  
device further comprises:

a transmitter oscillator having an enable input being  
configured to generate a carrier on which said information is  
carried;

a power amplifier having an enable input and being configured  
to amplify said carrier prior to transmission of said information  
which modulates said carrier; and

an enabling device connected to said enable input of said  
transmitter oscillator and said enable input of said power  
amplifier configured to enable an active state of said transmitter  
oscillator and said power amplifier during periods of information  
transmission and configured to place said transmitter oscillator  
and said power amplifier in a low current state during periods of  
non-transmission, thereby reducing current drain.

80. The system according to Claims 65, 66, 67, 68, 69, 70,  
73, 74, 75, 76, or 77, wherein said radio frequency transmit-only  
device further comprises:

a processor configured to generate said information to be  
transmitted; and

a wake-up circuit that maintains said processor in a reduced  
current state between transmissions, and upon expiration of said  
time duration, as determined by said timer, places said processor  
in a normal operational state.

<sup>17</sup>  
~~81~~. The system according to Claims ~~65~~, ~~66~~, ~~70~~, ~~73~~, or ~~74~~,  
wherein said radio frequency transmit-only device comprises a  
programming connector means for assigning said identification  
address to said radio frequency transmit-only device using a  
serial data stream.

<sup>18</sup>  
~~82~~. The system according to Claim ~~81~~,<sup>17</sup> further comprising a  
hand held terminal configured to load said identification address  
in the serial data stream to said programming connector.

<sup>19</sup>  
~~83~~. The system according to Claims ~~65~~, ~~66~~, ~~70~~, ~~73~~, or ~~74~~,  
wherein said timer is configured to divide said time duration into  
a very fine number of temporal time slots.

<sup>20</sup>  
~~84~~. The system according to Claims ~~65~~, ~~70~~, ~~73~~, or ~~74~~,  
wherein said radio frequency transmit-only device includes a  
programming connector means for assigning through a serial data  
stream said identification address, a type code, and a code  
division multiple access channel on which said radio frequency  
transmit-only device is to operate.

<sup>21</sup>  
~~85~~. The system according to Claims ~~66~~, ~~67~~, ~~70~~, ~~74~~, or ~~75~~,  
wherein said radio frequency transmit-only device comprises a data  
rate between 14 Kb/s and 21 Kb/s and a chip rate between <sup>1 MHz</sup>~~1.0 Mc/s~~  
and 1.3 <sup>MHz</sup> Mc/s.

<sup>22</sup>  
~~86~~. The system according to Claims ~~65~~, ~~66~~, ~~67~~, ~~68~~, ~~69~~, ~~70~~,

87. A remote power meter monitoring method, comprising the steps of:

- retrieving data from a sensing element;
- generating information containing the retrieved data, comprising,
  - generating an identification address field for holding an identification address corresponding to a transmit-only device, and
  - generating an error correction code;
- transmitting the generated information, redundantly at pseudo random intervals from said transmit-only device, comprising,
  - loading a timer with a pseudo random time interval value,
  - enabling, upon expiration of said timer, a crystal oscillator used to generate spread spectrum timing signals, a transmitter oscillator used to generate transmission signals,
  - delaying information transmission for a predetermined time period, relative to said expiration of said time interval, to allow for stabilization of said crystal oscillator and said transmitter oscillator,
  - transmitting a preamble portion of said information used for spread spectrum timing synchronization, said preamble having a length in bit times at least equal to a number of chips

40

in a chip code sequence used in direct sequence spread spectrum format by said transmit-only device,

transmitting the generated information in said direct sequence spread spectrum format based upon said chip code sequence and said spread spectrum timing signals at a predetermined frequency by said transmit-only device,

disabling said crystal oscillator and said transmitter oscillator, so as to conserve power;

repeating said step of transmitting said generated information redundantly after a pseudorandom interval of time so as to provide information transmission redundancy;

receiving the generated information by at least one receiver;

validating the received information based on said identification address and said error correction code;

transferring the validated information to a monitoring mechanism; and

monitoring the received data in the validated information with the monitoring mechanism.

<sup>26</sup>  
~~28~~. The method of Claim <sup>25</sup>~~27~~, wherein said step of generating information, comprises generating said information to have a data rate of approximately 14 Kb/s to 21 Kb/s and a chip rate of approximately 1 <sup>MHz to 1.3 MHz</sup> ~~Mcs to 1.3 Mc/s~~.

<sup>27</sup>  
~~29~~. The method according to Claim <sup>26</sup>~~27~~, further comprising the step of programming said identification address into said transmit-only device via a programming connector prior to

installing said transmit-only device.

<sup>28</sup>  
~~28~~. The method according to Claims <sup>25</sup>~~27~~ or <sup>26</sup>~~28~~, wherein said step of transmitting said generated information, redundantly comprises the substep of generating said preamble using a preamble chip code that is a same chip code sequence as that used with said received data.

<sup>29</sup>  
~~29~~. A remote power meter monitoring system, comprising:  
a multiplicity of radio frequency transmit-only devices configured to transmit information, each radio frequency transmit-only device comprising,

a timer configured to autonomously initiate transmission of said information after expiration of a time duration,

a random number generator configured to generate <sup>apseudo</sup>~~said pseudo~~ random time interval value and to cause the time interval between transmissions to be pseudorandom, and

a retransmission mechanism configured to retransmit said information a predetermined number of times;

at least one sensing element configured to provide sensor data gathered therein to said radio frequency transmit-only device, said transmitted information comprising said sensor data, an identification address being assigned to said radio frequency transmit-only device to which the sensor data is provided, and error detection code bits;

at least two receivers configured to receive said transmitted

Q2 Cont

060907Z  
060907Z  
060907Z

4

43

a retransmission mechanism configured to cause said information to be retransmitted a predetermined number of times,



and

a wake-up circuit configured to initiate said crystal oscillator and said processor in respective active states upon expiration of said time duration so as to transmit said information when in said respective active states, and configured to place said crystal oscillator and said processor in a reduced current state between transmission times;

at least one sensing element configured to provide sensor data to said radio frequency transmit-only device, said transmitted information comprising,

a data field that holds said sensor data,

an address field that holds an identification address being assigned to said radio frequency transmit-only device to which the sensor data is provided, and

an error field that holds error detection code bits;

at least two receivers each configured to receive said transmitted information, and configured to validate said information based on said identification address and said error detection code bits contained in said transmitted information, said receivers providing redundant reception of said transmitted information; and

a monitoring apparatus that is configured to monitor said information as received and validated by at least one of said receivers.

- 31  
25. A remote power meter monitoring system, comprising:  
a multiplicity of radio frequency transmit-only devices

configured to transmit information in a direct sequence spread spectrum signal at plural frequencies, said information comprising a first field comprising a preamble configured to establish chip code timing synchronization and a second field comprising data, said first field being transmitted prior to said second field, said preamble having a length measured in bit times that is at least equal in length to a number of chips in a chip code sequence used to produce said spread spectrum signal, each radio frequency transmit-only device comprising,

a timer configured to autonomously initiate transmission of said information after expiration of a time duration,

a random number generator that generates <sup>a pseudo</sup> ~~said pseudo~~ random time interval value and causes the time interval between transmissions to be psudeorandom, and

a retransmission mechanism configured to cause said information to be retransmitted a predetermined number of times;

at least one sensing element configured to provide sensor data to said radio frequency transmit-only device, said transmitted information comprising,

a data field that holds said sensor data,

an address field that holds an identification address being assigned to said radio frequency transmit-only device to which the sensor data is provided, and

an error field that holds error detection code bits;

at least two receivers each configured to receive said transmitted information, and configured to validate said

027  
Cmt

05859378 052697  
05859378 052697

information based on said identification address and said error detection code bits contained in said transmitted information, said receivers providing redundant reception of said transmitted information, said receivers configured to establish chip code synchronization to said direct sequence spread spectrum signal using said preamble; and

a monitoring apparatus that is configured to monitor said information as received and validated by at least one of said receivers.

*OB*  
*CH*  
<sup>32</sup>  
~~34~~. A remote power meter monitoring system, comprising:

06859378 052097  
a multiplicity of radio frequency transmit-only devices configured to transmit information in a direct sequence spread spectrum signal at plural frequencies, said information comprising a first field comprising a preamble configured to establish chip code timing synchronization and a second field comprising data, said first field being transmitted prior to said second field, said preamble having a length measured in bit times that is at least equal in length to a number of chips in a chip code sequence plus approximately five bit times, each radio frequency transmit-only device comprising,

a timer comprising a memory that holds a pseudo random time interval value, and configured to autonomously initiate transmission of said information after expiration of a time duration corresponding to said pseudo random time interval value held in said memory,

a random number generator configured to generate

666

said pseudo random time interval value and load said pseudo random time interval value into said timer, and

a retransmission device for redundantly transmitting said information a predetermined number of times;

at least one sensing element configured to provide sensor data to said radio frequency transmit-only device, said transmitted information comprising said sensor data, an identification address being assigned to said radio frequency transmit-only device to which the sensor data is provided, and error detection code bits;

at least two receivers each configured to receive said transmitted information, and configured to validate said information based on said identification address and said error detection code bits contained in said transmitted information, said receivers providing redundant reception of said transmitted information, said receivers configured to establish chip code lock and fine chip code synchronization using said preamble; and

a monitoring device for monitoring said information as received and validated by at least one of said receivers.

<sup>33</sup>  
~~25~~. A remote power meter monitoring system, comprising:

a multiplicity of radio frequency transmit-only devices configured to transmit information in a direct sequence spread spectrum signal at plural frequencies, said information comprising a first field comprising a preamble configured to establish chip code timing synchronization and a second field comprising data, said first field being transmitted prior to said second field,

ADD  
CMT  
08859378-052097

47

said preamble having a length measured in bit times that is less than n bit times, where n equals a number of chips in a chip code sequence, each radio frequency transmit-only device comprising,

a timer comprising a memory that holds a pseudo random time interval value, said timer configured to autonomously initiate transmission of said information after expiration of a time duration corresponding to said pseudo random time interval value held in said memory,

a random number generator configured to generate said pseudo random time interval value and for loading said pseudo random time interval value into said timer, and

a retransmission device for redundantly transmitting said information a predetermined number of times;

at least one sensing element configured to provide sensor data to said radio frequency transmit-only device, said transmitted information comprising,

a data field that holds said sensor data,

an address field that holds an identification address being assigned to said radio frequency transmit-only device to which the sensor data is provided, and

an error field that holds error detection code bits;

at least two receivers each configured to receive said transmitted information, and configured to validate said information based on said identification address and said error detection code bits contained in said transmitted information, said receivers providing redundant reception of said transmitted information, said receivers comprising respective parallel

00059378.052097  
269250

68